

Flow Time Measuring
Instrument
CUPTIMER
243 USB

with
USB interface
for
data storing



testing equipment for quality management



Technical Description

Opto-electronic Measuring Instrument for exact Determination of the Flow Time by using Standardized Flow Cups, for Viscosity Measurements

Design and Function

This opto-electronic measuring instrument offers a number of advantages to the user.

- Automatic measuring sequence with optical detection of the stream of sample.
- ◆ Flow times up to 1000 s can be read off from the LC display with a resolution up to 0.01 s.
- Equally suitable for all liquids (transparent calibration oils and opaque lacquers).
- Practical temperature adjustment:
 Temperature jacket removable from the basic unit; with adaptors for different shapes of flow cups.
- Easy to handle: One-button-operation.
- Designed as a mobile measuring station: sturdy, compact stand construction mounted on an adjustable base; plug-type tube connections; operated via plug-in supply unit.
- ♦ USB interface for storing the flow times on PC
- Power supply by USB interface, by choice also with plug-in supply unit

Technical Data

Dimensions:	Height	310 mm
(basic unit)	Width	200 mm
	Depth	280 mm

Weight, net: (basic unit) approx. 3 kg

USB power supply / plug-in supply unit:

primary current: 100-230 V AC secondary current: 5 V DC, 500 mA

Power consumption: approx. 0.8 VA

LC Display: 4 digits, with automatic

switch over between the ranges 99.99 s/ 999.9 s

Reference Class:

The CUPTIMER 243 USB is supplied with a Manufacturer's Certificate M in accordance with DIN 55 350-18 that includes among others the following information:

Result of the function test, accuracy of the time measuring device, product identification, test equipments used with calibration status, date, name of inspector.

Start and stop function are checked by transparent and opaque material. The accuracy of the time measuring device is determined by means of a digital radio controlled clock.

Order Information		
Order No.	Product Name	
03260131	Flow Time Measuring Instrument CUPTIMER 243 USB	
The	scope of supply includes:	
♦ U	SB plug-in supply unit	
 ◆ Spherical level 		
 Adaptors for DIN, ASTM and ISO flow 		
cups (also suitable for AFNOR cups)		
◆ Glass plate 75 x 110 mm		
 Temperature jacket 		
 Filling support stand (including 		
10 rubber caps to close the nozzle)		
♦ 0	perating instructions	
03260231	Flow Time Measuring Instrument	
	CUPTIMER 243 USB	
Th	ne scope of supply includes:	
 USB plug-in supply unit 		
 Spherical level 		
 Operating instructions 		

Accessories		
Order No.	Product Name	
00640231	Flow Cup acc. to DIN 53 211 (made of light metal) "REFERENCE CLASS" orifice dia. 4 mm	
00600131	Ford Flow Cup No. 2 acc. to ASTM D 1200 (made of anodized Aluminium) "REFERENCE CLASS"	
00600231	ditto, but No. 3	
00600331	ditto, but No. 4	
00610131	Flow Cup acc. to EN ISO 2431 (made of anodized Aluminium) "REFERENCE CLASS" orifice dia. 3 mm	
00610231	ditto, but orifice dia. 4 mm	
00610431	ditto, but orifice dia. 5 mm	
00610331	ditto, but orifice dia. 6 mm	

The right of technical modifications is reserved. Gr. 2 - TBE 243 USB – VIII/2019

